Amphenol Sensors

Connecting your world through Sensor Innovations

Heavy Vehicle & Off-Road (HVOR)

Amphenol Sensors is a leading innovator in sensor technologies and measurement solutions. Offering the most diverse sensor portfolio of standard and customized products for the world's most demanding regulatory and industry-driven applications, Amphenol creates value by providing critical information for real-time decisions.

Efficiency under high demand. For agriculture, farm, and construction, Amphenol Sensors combines its expertise in automotive sensors with the high demands inherent of heavy equipment.

Our sensors maximize the efficiency and lifetime of your heavy equipment, which translates to improved operational costs, operator safety and environmental compliance.



Amphenol Sensors

HVOR Sensor Solutions



Exhaust Gas Recirculation (EGR)

Battery Management Systems

Cylinder Head

MAP/TMAP Hydraulic Fluid

Powertrain Development

Transmission - E-Axle

ENGINE MANAGEMENT

Temperature Sensors

• High accuracy • High stability



Temposonics

PIHER sensing systems

THERMOMETRICS

SGX

EXATHERMOMETRICS

• Noise immune NTC option

• Fast response time • Combination sensor options

Pressure Sensors

• High accuracy • High performance



• Suitable for ambient temperatures up to 150°C

• Temperature measurement option

Position Sensors

• Absolute, non-contact measurement

- · Highest reliability
- Robust and compact design for harsh environments

Level, Concentration & Conductivity Sensors

- High accuracy
- Detects proper fluid fill and contaminant
- Customizable options

Current Sensors

• Based on open-loop Hall-effect and coreless TMR technology

- Busbar, integrated busbar, flanged and wire mounting
- Simple or redundant analog ratiometric output
- Measured values of up to ±4,000A

CABIN COMFORT

Temperature Sensors

- High accuracy High stability
- Noise immune NTC option
- Moisture resistant
- · Fast response time

Pressure Sensors

- High performance High accuracy
- Customizable design
- Multiple output options

Gas Detection Sensors

• Detectable gases: CO2, CO, NO2, NH3



Dew Point Sensors

- · Combined temperature and humidity measurement
- PWM and LIN bus
- · Custom package options

Dust Particulate Sensors

- PM2.5 Laser detection
- Fast response
 High accuracy

■ Passive Entry and Passive Start Systems

- Anti-theft Long-range PEPS
- Short-range immobilizer Encrypted CAN Bus
- CE/FCC certified

Position Sensors

PIHER sensing

Temposonics

PIEZOTRONICS

PCB PIEZOTRONICS

- Non-contact inductive and hall-effect technologies
- · Excellent resolution and precision
- · Reliable in harsh environments
- Touchless mechanical solutions

Position Sensors

- · Absolute, non-contact measurement
- Highest reliability
- Robust and compact design for harsh environments

Acoustic Sensors

- · Specialized microphones for a wide variety of applications
- High temperature, water and dust resistant models available
- · Highly accurate

Accelerometers

- Wide frequency ranges available
- Single and triaxial configurations
- · Robust design for demanding environments
- · Various mounting methods
- · Electrically isolated
- High sensitivity and low noise

Temperature Sensors

• High accuracy • High stability • Customized to application



POWERTRAIN



Temposonics

©PCB PIEZOTRONICS

© Temposonics

PIHER sensing

THERMOMETRICS

PIHER sensing systems

SGX

(i2s

EXATHERMOMETRICS

(i2s

• Utilizes metallurgical bond glass-coated NTC

- Stable and accurate Durable
- · Customizable design · Multiple output options

Position Sensors

- PIHER sensing • Non-contact inductive and hall-effect technologies
- · Excellent resolution and precision
- Reliable in harsh environments
- Touchless mechanical solutions

Position Sensors

- · Absolute, non-contact measurement
- Highest reliability
- Robust and compact design for harsh environments

■ Combined Pressure & Temperature Sensors

- High accuracy Oil resistant
- Wide temperature range: -40°C to 150°C
- Robust against pressure spikes

Accelerometers

- Wide frequency ranges available
- · Single and triaxial configurations
- Robust design for demanding environments
- · Various mounting methods
- · Electrically isolated
- High sensitivity and low noise

MOTION CONTROL & DRIVER ASSISTANT SYSTEMS

Position Sensors

- Absolute, non-contact measurement
- Highest reliability
- · Robust and compact design for harsh environments

SmartFlex

Sensor gateway and data logger

MAIRMAR

CHASSIS

- TPMS (Tire Pressure Monitoring System)
- High accuracy
- 24/7 operation
- CAN Bus integration
- Low power consumption: 7 years battery life
- Pressure range: up to 14 bar
- Autolocation feature

HVAC

Temperature Sensors

- High accuracy High stability
- Noise-immune NTC option
- Moisture resistant
- Fast response time

Position Sensors

- Robust and reliable modular design
- Custom form-factor available Selectable working principle:
- Potentiometric, hall effect, reed switch

Pressure Sensors

- Leakproof High accuracy
- Media compatibility

Gas Detection Sensors

- Detectable gases: CO2, CO, NO2, NH3
- PWM and LIN bus, custom packaging options

Dust Particulate Sensors

- PM2.5 Laser detection.
- · Custom packaging options

Combined Pressure & Temperature Sensors

- Compatible to coolants such as R134a, R1234yf, R744
- High accuracy and fast response time
- LIN output with diagnostic features
- Wide pressure range: 10 bar to 200 bar

SAFETY SYSTEMS

Temperature Sensors

- Fast response time High accuracy

 EXATHERMOMETRICS
- High stability
 Proven reliability
- Deep domain expertise Duplicate manufacturing locations
- Pressure Sensors
- High accuracy Small size
- Long-term stability
- Diagnostic and protective features (ASIL)

Position Sensors

- Robust and reliable modular design
- Selectable working principle: potentiometric, hall effect, reed switch

Position Sensors

- · Absolute, non-contact measurement
- Highest reliability
- Robust and compact design for harsh environments

Level & Concentration Sensors

- High accuracy
- · Continuous monitoring for fluid contamination
- Programmable for irregular shape tanks
- Customizable options

Accelerometers

- Wide frequency ranges available
- Single and triaxial configurations · Robust design for demanding environments
- · Various mounting methods
- Electrically isolated
- High sensitivity and low noise

Gas Detection Sensors

Detect the presence of combustible gases that indicate batteries Thermal Runaway conditions.

- Sensitivity to multiple gases: H₂/CO₂/NH₃/CO
- Temperature / Humidity Sensor
- Pressure sensor (20 up to 250 kPa)
- Fast response time: <1 second IP6K7 rating

Weatherstations®

- Hyper-local weather
- True wind speed and direction · GPS, heading, air temp, barometric pressure and
- relative humidity

FUEL HANDLING SYSTEM

Temperature Sensors

- · High accuracy
- High stability
- Integral/pigtail options Combination sensor options

Pressure Sensors

- · High accuracy
- High performance
- · Long-term stability Custom options

Position Sensors

- · Absolute, non-contact measurement
- Highest reliability
- Level Sensors
- · High accuracy
- Continuous monitoring
- Robust non-contacting sensors Slosh and aeration filtering software
- Diesel Flow Meter
- diesel engine systems
- Flow rates up to 4,000 liters per hour · Single and differential models

Continued on Next Page

PIHER sensing

THERMOMETRICS



®ENDEVCO (i2s























Mobile and stationary applications



















Fuel consumption measurement of







AFTER-TREATMENT

Temperature Sensors

- High accuracy High stability
- Integral/pigtail options
- Fast response time
- Right angle and straight probe options

DEF Level, Temperature & Concentration Sensors

- High accuracy
- Continuous monitoring
- Meets EPA regulations
- Programmable for irregular shape tank



N**□**V/\

THERMOMETRICS

EXATHERMOMETRICS

Pressure Sensors

- High reliability
- High accuracy
- Up/down stream pressure
- Customizable design
- Compatible with exhaust gas media and acid condensates



Scan the QR code to access our library of resources

www.amphenolsensors.com



© 2025 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.

Other company names and product names used in this document are the registered trademarks of their respective owners.